DEP7007 Forms (AI, EE, N and V)

11/2018 DEP7007AI

Divisio	Division for Air Qual		Γ	EP7007AI	Ado	Additional Documentation		
	Sower Boulev			strative Information AI.1: Source Information		tional Documentation attached		
	kfort, KY 406 502) 564-3999		Section	AI.2: Applicant Informa AI.3: Owner Information AI.4: Type of Application	n			
			Section	AI.5: Other Required In: AI.6: Signature Block AI.7: Notes, Comments,				
Source Name:		Buffalo Tra	ace Distillery, Inc.					
KY EIS (AFS) #	<u> </u>	21-073-000	09					
Permit #:		V-12-056						
Agency Interest	(AI) ID:	1373						
Date:		10/4/2019						
Section AI.1	: Source I	nformation						
Physical Location	Street:	113 Great B	Suffalo Trace					
Address:	City:	Frankfort		County: Franklin	Zip Code:	40601		
Mailing	Street or P.O. Box:	Same as phy	ysical address					
Address:	City:			State:	Zip Code:			
			Standard Coordina	ates for Source Physical	Location			
Longitude:		-84.871° E	(decimal degrees)	Latitude:	38.216694° N	_ (decimal degrees)		
Primary (NAICS) Category:	Distilleries		Primary NAI	ICS #: 312140			

EP7007AI Classification (SIC) Category: Distilled and Blended Liquors 2085 **Primary SIC #:** The site produces distilled spirits. Grain is delivered, ground, and introduced to mash cookers. The mash is fed to fermenters and then to Briefly discuss the type of business distillation columns and condensers. The resulting liquid is stored in tanks, transferred to barrels for aging, and/or sent to the bottling area for conducted at this site: packaging. Barrels of bourbon are stored in rick houses for aging. The spent grain is sold as distiller's dried grain. Beverage ingredients are received in bulk for blending, and other distilled spirits are received by the facility in bulk and sent to the bottling area for packaging. **Description of** Rural Area ☐ Industrial Park Residential Area Yes Is any part of the source Number of 474 Area located on federal land? **Employees:** ✓No ☑Commercial Area Urban Area ☐ Industrial Area Surrounding Approximate distance to nearest residence or **Property** 430 Acres Is this source portable? Yes 🗸 No commercial **Adjacent** Area: What other environmental permits or registrations does this source currently hold or need to obtain in Kentucky? Currently Hold NPDES/KPDES: N/A Need Currently Hold ✓ N/A **Solid Waste:** Need Currently Hold ✓ RCRA: Need N/A Currently Hold ✓ N/A UST: Need ☐ Mixed Waste Generator Other: Type of ☑ Generator Recycler **Regulated Waste Activity:** Transporter ☐ Treatment/Storage/Disposal Facility U.S. Importer of Hazardous Waste N/A

11/2018

11/2018 DEP7007AI

Section AI.2: Applicant Information								
Applicant Name:	Buffalo Trace Distiller	у						
Title: (if individual)								
Mailing Address:	Street or P.O. Box: City:	113 Great Buffa Frankfort	lo Trace State:	KY	Zip Code	40601		
Email: (if individual)			<u> </u>		_ · _			
Phone:	(502) 223-7641							
Technical Contact								
Name:	Andrew Leet							
Title:	Environmental Enginee	er						
Mailing Address:		113 Great Buffa Frankfort	lo Trace State:	KY	Zip Code	40601		
Email:	aleet@buffalotrace.com			KI		40001		
Phone:	(859) 705-8187							
Air Permit Contact fo	or Source							
Name:	Andrew Leet							
Title:	Environmental Enginee	er						
Mailing Address:	Street or P.O. Box: City:	113 Great Buffa Frankfort	lo Trace State:	KY	Zip Code	40601		
Email:	aleet@buffalotrace.com							
Phone:	(859) 705-8187							

11/2018

DEP7007AI

ection Al.3: Ov	wner Information			
☑ Owner same	e as applicant			
Name:				
Title:				
Mailing Address:	Street or P.O. Box:			
Maning Address:	City:	State:	Zip Code:	
Email:				
Phone:	_			
st names of owners a	and officers of the company who hav	e an interest in the company of 5% or	r more.	
	Name		Position	
	Wholly-owned subsid	iary of the Sazerac Company; New	Orleans, LA	

11/2018 DEP7007AI

Section AI.4: Ty	pe of Application							
Current Status:	✓ Title V ☐ Conditional	Major State-On	rigin		General Permit	☐ Registr	ration [None
Requested Action: (check all that apply) Requested Status:	Name Change ✓ Renewal Permit ☐ 502(b)(10)Change ☐ Revision ☐ Ownership Change ✓ Title V ☐ Conditional	Initial Registration Revised Registration Extension Request Off Permit Change Closure Major		Significant R Minor Revisi Addition of N Landfill Alter	on	☐ Initial S ☐ Portabl t ☐ Modifie	istrative Permit . Source-wide Ope e Plant Relocati cation of Existin	eratingPermit on Notice
Is the source requesting a limitation of potential emissions? Pollutant: Requested Limit: Particulate Matter				_ F	✓ No Pollutant: Single HAP		Requested Lin	nit:
 □ Volatile Organic Compounds (VOC) □ Carbon Monoxide □ Nitrogen Oxides □ Sulfur Dioxide □ Lead 				- [Combined HAPs Air Toxics (40 CFR 68) Carbon Dioxide Greenhouse Gases (GF) Other			
_	ction: rt Date of Construction: (MM/YYYY)			Propose	ed Operation Start-Up I	Pate:		
Proposed Sta	For Modifications: Proposed Start Date of Modification: (MM/YYYY) Proposed Operation Start-Up Date: (MM/YYYY)							
Applicant is seekir	Applicant is seeking coverage under a permit shield. Yes Identify any non-applicable requirements for which permit shield is sought on a separate attachment to the application.							

11/2018

DEP7007AI

Section AI.5 Other Required Information						
Indicate the documents at	tached a	as part of this application:				
DEP7007A Indirect Heat Exchangers and Turbines		DEP7007CC Compliance Certification				
DEP7007B Manufacturing or Processing Operations		DEP7007DD Insignificant Activities				
DEP7007C Incinerators and Waste Burners	J	DEP7007EE Internal Combustion Engines				
DEP7007F Episode Standby Plan		DEP7007FF Secondary Aluminum Processing				
☐ DEP7007J Volatile Liquid Storage		DEP7007GG Control Equipment				
☐ DEP7007K Surface Coating or Printing Operations		DEP7007HH Haul Roads				
DEP7007L Mineral Processes		Confidentiality Claim				
DEP7007M Metal Cleaning Degreasers		Ownership Change Form				
☑ DEP7007N Source Emissions Profile		Secretary of State Certificate				
☐ DEP7007P Perchloroethylene Dry Cleaning Systems		Flowcharts or diagrams depicting process				
DEP7007R Emission Offset Credit		Digital Line Graphs (DLG) files of buldings, roads, etc.				
☐ DEP7007S Service Stations		Site Map				
DEP7007T Metal Plating and Surface Treatment Operations		Map or drawing depicting location of facility				
☑ DEP7007V Applicable Requirements and Compliance Activities		Safety Data Sheet (SDS)				
DEP7007Y Good Engineering Practice and Stack Height Determination		Emergency Response Plan				
DEP7007AA Compliance Schedule for Non-complying Emission Units		Other:				
DEP7007BB Certified Progress Report						
Daile Wheath	l its attac ormation	chments. Based on my inquiry of those individuals with primary in is on knowledge and belief, true, accurate, and complete. I am ete information, including the possibility of fine or imprisonment. 10/4/2019				
Authorized Signature Harlen Wheatley		Date Master Distiller				
Type or Printed Name of Signatory		Title of Signatory				
*Responsible official as defined by 401 KAR 52:001.		or Signatury				

.8	Section AI.7: Notes, Comments, and Explanations	

DEP7007AI

Division for Air Quality

300 Sower Boulevard Frankfort, KY 40601 (502) 564-3999

1	n	\mathbf{F}	P'	70	U	7	\mathbf{F}°	\mathbf{F}
ı		1 ·				•	٠,	ı ،

Internal Combustion Engines

Section EE.1: General Information
Section EE.2: Operating Information
Section EE.3: Design Information

Section EE.4: Fuel Information
Section EE.5: Emission Factor Information

_ Section EE.6: Notes, Comments, and Explanations

Additional	Documentation
------------	----------------------

__ Complete DEP7007AI, DEP7007N, DEP7007V, and DEP7007GG

Attach EPA certification of the engine

Source Name: Buffalo Trace Distillery, Inc.

KY EIS (AFS) #: 21-073-00009

Permit #: V-12-056

Agency Interest (AI) ID: 1373

Date: 10/4/2019

Section EE.1: General Information

Emission Unit #	Emission Unit Name	Control Device ID	Stack ID	Manufacturer	Model Number	Model Year	Date of Manufacture	Proposed/Actual Date of Construction Commencement (MM/YYYY)	Date Reconstructed/ Modified	List Applicable Regulations
18_001	Emergency Generator Engine G001	na	S18A	Generac	SG070	2007	9/24/2007	2007	na	40 CFR 60 Subpart JJJJ (Gap Engine)
18_002	Emergency Generator Engine G002	na	S18B	Cummins	75GGHF	2006	5/1/2006	2006	na	40 CFR 63 Subpart ZZZZ (Existing Engine)
					D 0					

Section EE.2: Operating Information										
Engine Purpose (Identify if Non-Emergency, Emergency,Fire/Water Pump, Black-start engine for combustion turbine, Engine Testing)	Hours Operated	Is this engine a rental? (Yes/No)	Rental Time Period (hrs)	Alternate Operating Scenarios (Describe any operating scenarios in which the engine may be used in a different configuration)						
Emergency	500	No	na							
Emergency	500	No	na							
	Engine Purpose (Identify if Non-Emergency, Emergency,Fire/Water Pump, Black-start engine for combustion turbine, Engine Testing) Emergency	Engine Purpose (Identify if Non-Emergency, Emergency,Fire/Water Pump, Black-start engine for combustion turbine, Engine Testing) Hours Operated 500	Engine Purpose (Identify if Non-Emergency, Emergency,Fire/Water Pump, Black-start engine for combustion turbine, Engine Testing) Hours Operated rental? (Yes/No) Emergency 500 No	Engine Purpose (Identify if Non-Emergency, Emergency,Fire/Water Pump, Black-start engine for combustion turbine, Engine Testing) Hours Operated rental? (Yes/No) Emergency 500 No na						

Section EE.3	: Design Information						
Emission Unit#	Engine Type (Identify all that apply: Commercial, Institutional, Stationary, Non-Road)	Ignition Type (Identify if either Compression or Spark Ignition)	Engine Family (Identify all that apply: 2- stroke, 4-stroke, Rich Burn, Lean Burn)	Maximum Engine Power (bhp)	Maximum Engine Speed (rpm)	Total Displacement	Number of Cylinders
18_001	Stationary	Spark Ignition	4-Stroke, Lean Burn	107	1,800	7	10
18_002	Stationary	Spark Ignition	4-Stroke, Lean Burn	126	1,800	7	10

Section EE. 4	Section EE.4: Fuel Information										
Emission Unit #	Identify if Primary, Secondary, or Tertiary Fuel	Fuel Type (Identify if Diesel, Gasoline, Natural Gas, Liquefied Petroleum Gas (LPG), Landfill/Digester Gas, or Other)	Fuel Grade	Percent Time Used (%)	Maximum Fuel Consumption	Heat Content	Sulfur Content	SCC Code	SCC Units		
18_001	Primary	Natural Gas	na	100	1,009 scf/hr	1020 Btu/scf	Neg.	20200202	MMcf NG Burned		
18_002	Primary	Natural Gas	na	100	1,017 scf/hr	1020 Btu/scf	Neg.	20200202	MMcf NG Burned		

Section EE.5: Emission Factor Information

Emission factors expressed here are based on the potential to emit.

Emission Unit #	Fuel	Pollutant	Emission Factor	Emission Factor Units	Source of Emission Factor
18_001	Primary	PM/PM10/PM2.5	10.2	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_001	Primary	NOx	4,162	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_001	Primary	SO2	0.60	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_001	Primary	VOC	120	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_001	Primary	СО	323	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_001	Primary	CO2	119,317	lb/MMcf NG Burned	40 CFR 98, Subpart C, Table C-1
18_001	Primary	N2O	0.22	lb/MMcf NG Burned	40 CFR 98, Subpart C, Table C-2
18_001	Primary	CH4	2.25	lb/MMcf NG Burned	40 CFR 98, Subpart C, Table C-2
18_001	Primary	Formaldehyde	53.9	lb/MMcf NG Burned	AP-42 Table 3.2-2
18_001	Primary	Ammonia	18.0	lb/MMcf NG Burned	SCAQMD Document, 12/2016
18_001	Primary	Lead	5.00E-04	lb/MMcf NG Burned	AP-42 Table 1.4-2
18_002	Primary	PM/PM10/PM2.5	10.2	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_002	Primary	NOx	4,162	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_002	Primary	SO2	0.60	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_002	Primary	VOC	120	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000

Emission Unit #	Fuel	Pollutant	Emission Factor	Emission Factor	Source of Emission Factor
18_002	Primary	СО	323	lb/MMcf NG Burned	AP-42 Table 3.2-2, 07/2000
18_002	Primary	CO2	119,317	lb/MMcf NG Burned	40 CFR 98, Subpart C, Table C-1
18_002	Primary	N2O	0.22	lb/MMcf NG Burned	40 CFR 98, Subpart C, Table C-2
18_002	Primary	CH4	2.25	lb/MMcf NG Burned	40 CFR 98, Subpart C, Table C-2
18_002	Primary	Formaldehyde	53.9	lb/MMcf NG Burned	AP-42 Table 3.2-2
18_002	Primary	Ammonia	18.0	lb/MMcf NG Burned	SCAQMD Document, 12/2016
18_002	Primary	Lead	5.00E-04	lb/MMcf NG Burned	AP-42 Table 1.4-2

Section EE.6: Notes, Comments, and Explanations

Division for Air Quality

300 Sower Boulevard Frankfort, KY 40601 (502) 564-3999

DE	P7	'n	17	
עוכו	. /	w	,	' I '

Source Emissions Profile

Section N.1: Emission SummarySection N.2: Stack InformationSection N.3: Fugitive Information

Buffalo Trace Distillery, Inc.

21-073-00009 V-12-056

1373

10/4/2019

__ Section N.4: Notes, Comments, and Explanations

Additional	Documentation
------------	---------------

_ Complete DEP7007AI

N.1: Emission	Summary
---------------	---------

Agency Interest (AI) ID:

Source Name: KY EIS (AFS) #:

Permit #:

Date:

	,		ſ						ı		1	1				
Emission	Emission Unit Name	Process	Process Name	Control Device	Control Device	Stock	Maximum Design	Pollutant	Uncontrolled Emission	Emission Factor Source (e.g. AP-	Capture Efficiency	Control	Hourly Emissions		Annual Emissions	
Unit #	Emission Unit Name	ID	Frocess Name	Name	ID	ID	Capacity (SCC Units/hour)	ronutant	Factor (lb/SCC Units)	42, Stack Test, Mass Balance)	(%)	(%)	Uncontrolled Potential (lb/hr)	Controlled Potential (lb/hr)	Uncontrolle d Potential (tons/yr)	Controlled Potential (tons/yr)
18_001	Emergency Generator Engine G001	1	Natural Gas Combustion	na	na	S18A	1.009E-03	PM/PM10/PM2.5	10.2	AP-42 Table 3.2-2, 07/2000	na	na	0.01	na	0.003	na
								NOx	4,162	AP-42 Table 3.2-2, 07/2000	na	na	4.20	na	1.05	na
								SO2	0.60	AP-42 Table 3.2-2, 07/2000	na	na	0.001	na	0.0002	na
								VOC	120	AP-42 Table 3.2-2, 07/2000	na	na	0.12	na	0.03	na
								СО	323	AP-42 Table 3.2-2, 07/2000	na	na	0.33	na	0.08	na
								CO2	119,317	40 CFR 98, Subpart C, Table C-1	na	na	120.39	na	30.10	na
								N2O	0.22	40 CFR 98, Subpart C, Table C-2	na	na	2.27E-04	na	5.67E-05	na
								CH4	2.25	40 CFR 98, Subpart C, Table C-2	na	na	0.002	na	0.001	na
								Formaldehyde	53.9	AP-42 Table 3.2-2	na	na	0.05	na	0.01	na
								Ammonia	18.0	SCAQMD Document, 12/2016	na	na	0.02	na	0.005	na
								Lead	5.00E-04	AP-42 Table 1.4-2	na	na	5.05E-07	na	1.26E-07	na

18_002	Emergency Generator Engine G002	1	Natural Gas Combustion	na	na	S18B	1.017E-03	PM/PM10/PM2.5	10.2	AP-42 Table 3.2-2, 07/2000	na	na	0.01	na	0.003	na
								NOx	4,162	AP-42 Table 3.2-2, 07/2000	na	na	4.23	na	1.06	na
								SO2	0.60	AP-42 Table 3.2-2, 07/2000	na	na	0.001	na	0.0002	na
								VOC	120	AP-42 Table 3.2-2, 07/2000	na	na	0.12	na	0.03	na
								СО	323	AP-42 Table 3.2-2, 07/2000	na	na	0.33	na	0.08	na
								CO2	119,317	40 CFR 98, Subpart C, Table C-1	na	na	121.36	na	30.34	na
								N2O	0.22	40 CFR 98, Subpart C, Table C-2	na	na	2.29E-04	na	5.72E-05	na
								CH4	2.25	40 CFR 98, Subpart C, Table C-2	na	na	0.002	na	0.001	na
								Formaldehyde	53.9	AP-42 Table 3.2-2	na	na	0.05	na	0.01	na
								Ammonia	18.0	SCAQMD Document, 12/2016	na	na	0.02	na	0.005	na
								Lead	5.00E-04	AP-42 Table 1.4-2	na	na	5.09E-07	na	1.27E-07	na

Section N.2: Stack Information

UTM Zone: 16

0. 1.	Identify all Emission Units (with Process ID) and	Sta	ck Physical D	ata	Stack UTM	Coordinates	Stack Gas Stream Data			
Stack ID	Control Devices that Feed to Stack	Equivalent Diameter (ft)	Height (ft)	Base Elevation (ft)	Northing (m)	Easting (m)	Flowrate (acfm)	Temperature (°F)	Exit Velocity (ft/sec)	
S18A	18_001	0.17	4.7	505	4,231,873	686,300	680	1,250	519	
S18B	18_002	0.17	4.7	505	4,231,873	686,300	539	1,233	412	

JTM Zone:									
			Area Physi	cal Data	Area UTM	Coordinates	Area Release Data		
Emission Unit #	Emission Unit Name	Process ID	Length of the X Side (ft)	Length of the Y Side (ft)	Northing (m)	Easting (m)	Release Temperature	Release Height	
			Not Applicable for	this Application		•			

Section N.4: Notes, Comments, and Explanations
The base height and UTM coordinates represent the approximate centerpoint of the Buffalo Trace distillery. G001 is located in the process chiller area; G002 is located near the control room for the distillery.
Manufacturer's information is used for the G001 stack height. G002 is assumed to have a similar stack. Engineering estimates are used for other stack parameters.
The stack location information presented in Section N.2 represents the approximate centerpoint of the facility.

Division for Air Quality

300 Sower Boulevard Frankfort, KY 40601 (502) 564-3999

Source Name:

Permit #:

Date:

KY EIS (AFS) #:

Agency Interest (AI) ID:

DEP7007V

Applicable Requirements and Compliance Activities

 Section V.1: Emission and Operating Limitation(s)
 Section V.2: Monitoring Requirements
 Section V.3: Recordkeeping Requirements
 Section V.4: Reporting Requirements
 Section V.5: Testing Requirements
Section V.6: Notes, Comments, and Explanations

Additional	Documentation
------------	----------------------

Complete DEP7007AI

Section V.1: Emission and Operating Limitation(s)

Buffalo Trace Distillery, Inc.

21-073-00009

V-12-056

1373 10/4/2019

Emission Unit#	Emission Unit Description	Applicable Regulation or Requirement	Pollutant	Emission Limit (if applicable)	Voluntary Emission Limit or Exemption (if applicable)	Operating Requirement or Limitation (if applicable)	Method of Determining Compliance with the Emission and Operating Requirement(s)
18_001	Emergency Generator Engine G001	NESHAP ZZZZ: 40 CFR 63.6590(c)	na	na		Because construction commenced after June 12, 2006, G001 is considered to be a new stationary RICE at an area source. Therefore, BTD meets the requirements of NESHAP ZZZZ by complying with NSPS JJJJ.	Comply with NSPS JJJJ requirements.
18_001	Emergency Generator Engine G001	NSPS JJJJ: 40 CFR 60.4230(a)(4)(iv)	na	na	na	G001 was manufactured by Generac in September 2007. 40 CFR 60.4230(a)(4)(iv) specifies that an emergency engine with a maximum engine power greater than 25 HP is subject to the requirements of this subpart only if it is manufactured on or after January 1, 2009. Since G001 was manufactured before January 1, 2009, no specific Subpart JJJJ requirements apply (in spite of the engine being generally subject to this regulation).	Although G001 is generally subject to NSPS JJJJ (and compliance with NESHAP ZZZZ is demonstrated by complying with NSPS JJJJ), no specific NSPS JJJJ requirements apply. Therefore, G001 is considered to be a NSPS JJJJ gap engine.

Emission Unit#	Emission Unit Description	Applicable Regulation or Requirement	Pollutant	Emission Limit (if applicable)	Voluntary Emission Limit or Exemption (if applicable)	Operating Requirement or Limitation (if applicable)	Method of Determining Compliance with the Emission and Operating Requirement(s)
18_001	Emergency Generator Engine G001	NSPS JJJJ: 40 CFR 60.4243(d)	na	na	na	Operate according to the requirements in (d)(1) through (3) to be considered an emergency stationary ICE (i.e., no time limit on emergency operations; up to 100 hours per calendar year of maintenance checks and readiness testing, as part of emergency demand response, and for voltage or frequency deviations; up to 50 hours per calendar year for non-emergency situations.).	To preclude the applicability of federal requirements for non- emergency engines, monitor hours of operation in emergency and non-emergency service and the reason the engine was in operation during that time.
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: 40 CFR 63.6590(a)(1)(iii); 63.6590(c)(1)	na	na	na	Per its nameplate, G002 was built in May 2006 and began operating at BTD on July 18, 2006. NESHAP ZZZZ distinguishes between new and existing units based on whether the unit was installed before or after June 12, 2006. If G002 was installed after June 12, 2006, then it is a gap engine that falls in the same category as G001 and doesn't have specifically applicable requirements under NSPS JJJJ. BTD was not able to identify the actual installation date for G002. As such, because the date the engine became operational at BTD is within 30 days of the applicable engine classification date, BTD has conservatively assumed that G002 is classified as an existing engine and is subject to NESHAP ZZZZ requirements.	Comply with NESHAP ZZZZ requirements.

Emission Unit #	Emission Unit Description	Applicable Regulation or Requirement	Pollutant	Emission Limit (if applicable)	Voluntary Emission Limit or Exemption (if applicable)	Operating Requirement or Limitation (if applicable)	Method of Determining Compliance with the Emission and Operating Requirement(s)
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: 40 CFR 63.6640(f)	na	na	na	Operate according to the requirements in (f)(1), (2), and (4) to be considered an emergency stationary RICE (i.e., no time limit on emergency operations; up to 100 hours per calendar year of maintenance checks and readiness testing, as part of emergency demand response, and for voltage or frequency deviations; up to 50 hours per calendar year for non-emergency situations.).	Monitor operating hours and reason to demonstrate compliance with these limits.
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: 40 CFR 63.6605(b)	na	na	na	Operate and maintain the engine in a manner consistent with safety and good air pollution control practices for minimizing emissions.	Follow manufacturer's operating instructions.
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: 40 CFR 63.6625(e)	na	na	na	Operate and maintain the unit according to manufacturer's emission-related written instructions or your own maintenance plan.	Follow manufacturer's operating instructions.
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: 40 CFR 63.6625(h)	na	na	na	Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.	Follow manufacturer's operating instructions.
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: Table 2d	na	na	na	If the engine is operating for emergency purposes when maintenance is required, perform the required maintenance as soon as practicable after the emergency has ended.	Ensure that operators understand and are trained to comply with this requirement.

Emission Unit #	Emission Unit Description	Applicable Regulation or Requirement	Pollutant	Emission Limit (if applicable)	Voluntary Emission Limit or Exemption (if applicable)	Operating Requirement or Limitation (if applicable)	Method of Determining Compliance with the Emission and Operating Requirement(s)
18_002	Emergency Generator Engine G002	NESHAP ZZZZ: Table 2d & 40 CFR 63.6625(j)	na	na	na		Complete and document required maintenance.

Section V.2: Monitoring Requirements

	8	I			
Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Monitored	Description of Monitoring
18_001	Emergency Generator Engine G001	na	na	Operating Hours	To preclude the applicability of federal requirements for non-emergency engines, BTD will use a non-resettable hour meter to monitor G001's operating time to demonstrate that it qualifies as an emergency engine. (Note: the non-resettable operating hour meter requirement of 40 CFR 60.4237(c) does not apply to G001 based on its rated capacity and build date).
18_002	Emergency Generator Engine G002	na	NESHAP ZZZZ: 40 CFR 63.6625(f)	Operating Hours	Install a non-resettable hour meter to monitor G002's operating time.

Section V.3: Recordkeeping Requirements

Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Recorded	Description of Recordkeeping
18_001	Emergency Generator Engine G001	na	na	Operating Hours	To preclude the applicability of federal requirements for non-emergency engines, BTD will record G001's annual operating hours and the purpose of operation to demonstrate that it qualifies as an emergency engine.
18_002	Emergency Generator Engine G002	na	NESHAP ZZZZ: 40 CFR 63.6655(f)	Operating Hours	Maintain records of the operation of the engine in emergency and non- emergency service that are recorded through the non-resettable hour meter. Record the time of operation of the engine and the reason the engine was in operation during that time.
18_002	Emergency Generator Engine G002	na	NESHAP ZZZZ: 40 CFR 63.6655(e)	Maintenance Conducted	Keep records of the maintenance conducted on G002 in order to demonstrate that you operated and maintained the engine according to manufacturer's emission-related written instructions or BTD's maintenance plan.

Section V.4: Reporting Requirements

Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Reported	Description of Reporting
na	na	na	na	na	na

Section V.5: Testing Requirements

Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Tested	Description of Testing
na	na	na	na	na	na

Section V.6: Notes, Comments, and Explanations					

ATTACHMENT B

Emission Calculations

B-1. Emissions Associated with Generac SG070 Generator Engine (G001)

B-1.1 Generator Power and Fuel Consumption Data

> Pertinent data on engine power and fuel usage taken from the technical data sheet and statement of exhaust for the Generac SG070 generator.

Engine Output in hp (100% load, standby): 107.0 bhp
Generator Output in kW (100% load, standby): 70.0 kW
Fuel Consumption Rate in scf/hr (100% load, standby): 1,009.0 scf/hr
Annual Operating Hours: 500 hrs
Heat Content of Natural Gas (HHV): 1,020 Btu/scf

B-1.2 Source Classification Code

> Emissions are tied to the SCC code for natural gas fueled engines listed below.

SCC: 20200202

SCC Description: Internal Combustion Engines, Industrial (2-02), Natural Gas (2-02-002), Reciprocating (2-02-002-02)

SCC Units: Million Cubic Feet Natural Gas Burned

B-1.3 Rich/Lean Burn Engine Determination

> Emissions for natural gas/propane-fired engines are directly linked to the air-to-fuel ratio and as such, emission factors in AP-42 are delineated into separate tables for rich and lean burn engines. The air-to-fuel ratio is calculated below to determine which of these emission factor sets are more appropriate.

	Value	Units	Basis
Combustion Air in cfh:	12,780 cfh		Manufacturer Specification Sheet
Density of Air in lb/cf:	0.076 lb/c	f	At sea level at 15 C (60 F)
Fuel consumption rate in cfh (100% load):	1,009.0 cfh		Manufacturer Specification Sheet
Density of Natural Gas in lb/cf:	0.042 lb/c	f	AP-42 Appendix A, Misc. Data and Conversion Factors
Operating Air-to-Fuel Ratio (AFR):	22.91		= (12,780 cfh * 0.076 lb/cf) / (1009.0 cfh * 0.042 lb/cf)
Stoichiometric AFR:	14.50		John B. Heywood: "Internal Combustion Engine Fundamentals page 915", 1988
AFR Ratio:	1.58		= (22.91 / 14.50)

> According to 40 CFR 60.4248, rich-burn engines are defined as any four-stroke spark ignited engine where the operating air/fuel ratio divided by the stoichiometric air/fuel ratio at full load conditions is less than or equal to 1.1. Lean-burn engines are defined as any two-stroke or four-stroke spark ignited engine that does not meet the definition of a rich burn engine. Therefore, the engine integral to this generator set is classified as a lean-burn engine when combusting natural gas fuel and the emission factors for AP-42 Table 3.2-2 apply.

B-1.4 Emission Calculation Methodology and Emission Factors

> Emission factors are from AP-42 Section 3.2 (7/2000) Table 3.2-2 Uncontrolled Emission Factors for 4-Stroke Lean-Burn Engines. Conservatively over-estimating PM by assuming PM is equal to PM10/PM2.5.

B-1.4.1 NOX

Emission factor for NOX:	4.08 lb/MMBtu	AP-42 Table 3.2-2, 07/2000
NOX emission factor in terms of SCC units:	4,161.60 lb/MMscf	= 4.08 lb/MMBtu * 1020 Btu/scf
B-1.4.2 CO		
Emission factor for CO:	0.32 lb/MMBtu	AP-42 Table 3.2-2, 07/2000
CO emission factor in terms of SCC units:	323.34 lb/MMscf	= 0.32 lb/MMBtu * 1020 Btu/scf
B-1.4.3 VOC		
Emission factor for VOC:	0.12 lb/MMBtu	AP-42 Table 3.2-2, 07/2000
VOC emission factor in terms of SCC units:	120.36 lb/MMscf	= 0.12 lb/MMBtu * 1020 Btu/scf
B-1.4.4 PM/PM10/PM2.5		
Emission factor for PM:	9.99E-03 lb/MMBtu	AP-42 Table 3.2-2, 07/2000
PM emission factor in terms of SCC units:	10.19 lb/MMscf	= 9.99E-03 lb/MMBtu * 1020 Btu/scf
B-1.4.5 SO2		
Emission factor for SO2:	5.88E-04 lb/MMBtu	AP-42 Table 3.2-2, 07/2000
SO2 emission factor in terms of SCC units:	0.60 lb/MMscf	= 5.88E-04 lb/MMBtu * 1020 Btu/scf

B-1.4.6 HAP Emission Estimates

> Formaldehyde emission factor is from AP-42 Section 3.2 Table 3.2-2 Uncontrolled Emission Factors for 4-Stroke Lean-Burn Engines, ammonia emission factor is from South Coast Air Quality Management District (SCAQMD) Reporting Procedures for AB2588 Facilities for Reporting Their Quadrennial Air Toxics Emissions Inventory from 12/2016, and lead is from AP-42 Section 1.4 Table 1.4-2.

			Emission Factor	Emission Factor	
	CAS#	HAP?	(lb/MMBtu)	(lb/MMscf)	Emission Factor Basis
Formaldehyde	50-00-0	Υ	0.053	53.86	AP-42 Table 3.2-2
Ammonia	7664-41-7	N	0.018	18.00	SCAQMD Document, 12/2016
Lead	7439-92-1	Υ	4.90E-07	5.00E-04	AP-42 Table 1.4-2

B-1.4.7 GHG Emission Factors

> CO2, CH4 and N2O emissions for natural gas combustion are estimated using the natural gas emission factors published in 40 CFR 98, Subpart C, Table C-1 and C-2.

Global Warming Potentials of GHGs per 40 CFR 98 Subpart A, Table A-1.

CO2 1 CH4 25 N2O 298

CO2 Emission Factor 53.06 kg CO2/MMBtu 40 CFR 98, Subpart C, Table C-1; Natural Gas (weighted U.S. average)
CH4 Emission Factor 1.0E-03 kg CH4/MMBtu 40 CFR 98, Subpart C, Table C-2; Natural Gas
N2O Emission Factor 1.0E-04 kg N2O/MMBtu 40 CFR 98, Subpart C, Table C-2; Natural Gas

Emission Equivalent Factor Factor (kg/MMBtu) (lb/MMscf) Pollutant CO2 53.06 119,317 CH4 1.00E-03 N2O 1.00E-04 0.22 CO2e 53.11 119,440

B-1.5 Summary of Engine Potential Emissions

	Emission Factor		Hourly Emissions	Annual Emissions
Pollutant	(lb/MMscf)	Basis	(lb/hr)	(tpy)
NOX	4,161.60	AP-42 Table 3.2-2, 07/2000	4.20	1.05
CO	323.34	AP-42 Table 3.2-2, 07/2000	0.33	0.082
VOC	120.36	AP-42 Table 3.2-2, 07/2000	0.12	0.030
PM/PM10/PM2.5	10.19	AP-42 Table 3.2-2, 07/2000	1.03E-02	2.57E-03
SO2	0.60	AP-42 Table 3.2-2, 07/2000	6.05E-04	1.51E-04
Formaldehyde	53.86	AP-42 Table 3.2-2	0.054	0.014
Ammonia	18.00	SCAQMD Document, 12/2016	0.018	4.54E-03
Lead	5.00E-04	AP-42 Table 1.4-2	5.05E-07	1.26E-07
CO2	119,317	40 CFR 98, Subpart C, Table C-1	120.39	30.10
CH4	2.25	40 CFR 98, Subpart C, Table C-2	2.27E-03	5.67E-04
N2O	0.22	40 CFR 98, Subpart C, Table C-2	2.27E-04	5.67E-05
CO2e	119,440	40 CFR 98, Subpart C	120.52	30.13

B-2. Emissions Associated with Cummins 75GGHF Generator Engine (G002)

B-2.1 Generator Power and Fuel Consumption Data

> Pertinent data on engine power and fuel usage taken from the technical data sheet and statement of exhaust for the Cummins 75GGHF generator.

Engine Output in hp (100% load, standby):126.0 bhpGenerator Output in kW (100% load, standby):70.0 kWFuel Consumption Rate in scf/hr (100% load, standby):928.3 scf/hrAnnual Operating Hours:500 hrsHeat Content of Natural Gas (HHV):1,020 Btu/scf

B-2.2 Source Classification Code

> Emissions are tied to the SCC code for natural gas fueled engines listed below.

SCC: 20200202

SCC Description: Internal Combustion Engines, Industrial (2-02), Natural Gas (2-02-002), Reciprocating (2-02-002-02)

SCC Units: Million Cubic Feet Natural Gas Burned

B-2.3 Rich/Lean Burn Engine Determination

> Emissions for natural gas/propane-fired engines are directly linked to the air-to-fuel ratio and as such, emission factors in AP-42 are delineated into separate tables for rich and lean burn engines. The air-to-fuel ratio is calculated below to determine which of these emission factor sets are more appropriate.

	Value	Units	Basis
Operating Air-to-Fuel Ratio (AFR):	16.20		Manufacturer Specification Sheet
Stoichiometric AFR:	14.50		John B. Heywood: "Internal Combustion Engine Fundamentals page 915", 1988
AFR Ratio:	1.12		= (16.20 / 14.50)

> According to 40 CFR 60.4248, rich-burn engines are defined as any four-stroke spark ignited engine where the operating air/fuel ratio divided by the stoichiometric air/fuel ratio at full load conditions is less than or equal to 1.1. Lean-burn engines are defined as any two-stroke or four-stroke spark ignited engine that does not meet the definition of a rich burn engine. Therefore, the engine integral to this generator set is classified as a lean-burn engine when combusting natural gas fuel and the emission factors for AP-42 Table 3.2-2 apply.

B-2.4 Emission Calculation Methodology and Emission Factors

> Emission factors are from AP-42 Section 3.2 (7/2000) Table 3.2-2 Uncontrolled Emission Factors for 4-Stroke Lean-Burn Engines. Conservatively over-estimating PM by assuming PM is equal to PM10/PM2.5.

B-2.4.1 NOX

Emission factor for NOX:	4.08 lb/MMBtu	AP-42 Table 3.2-2, 07/2000	
NOX emission factor in terms of SCC units:	4,161.60 lb/MMscf	= 4.08 lb/MMBtu * 1020 Btu/scf	
B-2.4.2 CO			
Emission factor for CO:	0.32 lb/MMBtu	AP-42 Table 3.2-2, 07/2000	
CO emission factor in terms of SCC units:	323.34 lb/MMscf	= 0.32 lb/MMBtu * 1020 Btu/scf	
B-2.4.3 VOC			
Emission factor for VOC:	0.12 lb/MMBtu	AP-42 Table 3.2-2, 07/2000	
VOC emission factor in terms of SCC units:	120.36 lb/MMscf = 0.12 lb/MMBtu * 1020 Btu/		
B-2.4.4 PM/PM10/PM2.5			
Emission factor for PM:	9.99E-03 lb/MMBtu	AP-42 Table 3.2-2, 07/2000	
PM emission factor in terms of SCC units:	10.19 lb/MMscf	= 9.99E-03 lb/MMBtu * 1020 Btu/scf	
B-2.4.5 SO2			
Emission factor for SO2:	5.88E-04 lb/MMBtu	AP-42 Table 3.2-2, 07/2000	
SO2 emission factor in terms of SCC units:	0.60 lb/MMscf	= 5.88E-04 lb/MMBtu * 1020 Btu/scf	

B-2.4.6 HAP Emission Estimates

> Formaldehyde emission factor is from AP-42 Section 3.2 Table 3.2-2 Uncontrolled Emission Factors for 4-Stroke Lean-Burn Engines, ammonia emission factor is from South Coast Air Quality Management District (SCAQMD) Reporting Procedures for AB2588 Facilities for Reporting Their Quadrennial Air Toxics Emissions Inventory from 12/2016, and lead is from AP-42 Section 1.4 Table 1.4-2.

	CAS#	HAP?	Emission Factor (lb/MMBtu)	Emission Factor (lb/MMscf)	Emission Factor Basis
Formaldehyde	50-00-0	Y	0.053	53.86	AP-42 Table 3.2-2
Ammonia	7664-41-7	N	0.018	18.00	SCAQMD Document, 12/2016
Lead	7439-92-1	Υ	4.90E-07	5.00E-04	AP-42 Table 1.4-2

B-2.4.7 GHG Emission Factors

> CO2, CH4 and N2O emissions for natural gas combustion are estimated using the natural gas emission factors published in 40 CFR 98, Subpart C, Table C-1 and C-2.

Global Warming Potentials of GHGs per 40 CFR 98 Subpart A, Table A-1.

CO2	1
CH4	25
N2O	298

CO2 Emission Factor 53.06 kg CO2/MMBtu 40 CFR 98, Subpart C, Table C-1; Natural Gas (weighted U.S. average)
CH4 Emission Factor 1.0E-03 kg CH4/MMBtu 40 CFR 98, Subpart C, Table C-2; Natural Gas
N2O Emission Factor 1.0E-04 kg N2O/MMBtu 40 CFR 98, Subpart C, Table C-2; Natural Gas

	Emission Factor	Equivalent Factor
Pollutant	(kg/MMBtu)	(lb/MMscf)
CO2	53.06	119,317
CH4	1.00E-03	2.25
N2O	1.00E-04	0.22
CO26	53 11	119 440

B-2.5 Summary of Engine Potential Emissions

	Emission		Hourly	Annual
	Factor		Emissions	Emissions
Pollutant	(lb/MMscf)	Basis	(lb/hr)	(tpy)
NOX	4,161.60	AP-42 Table 3.2-2, 07/2000	3.86	0.97
CO	323.34	AP-42 Table 3.2-2, 07/2000	0.30	0.075
VOC	120.36	AP-42 Table 3.2-2, 07/2000	0.11	0.028
PM/PM10/PM2.5	10.19	AP-42 Table 3.2-2, 07/2000	9.46E-03	2.36E-03
SO2	0.60	AP-42 Table 3.2-2, 07/2000	5.57E-04	1.39E-04
Formaldehyde	53.86	AP-42 Table 3.2-2	0.050	0.012
Ammonia	18.00	SCAQMD Document, 12/2016	0.017	4.18E-03
Lead	5.00E-04	AP-42 Table 1.4-2	4.64E-07	1.16E-07
CO2	119,317	40 CFR 98, Subpart C, Table C-1	110.76	27.69
CH4	2.25	40 CFR 98, Subpart C, Table C-2	2.09E-03	5.22E-04
N2O	0.22	40 CFR 98, Subpart C, Table C-2	2.09E-04	5.22E-05
CO2e	119,440	40 CFR 98, Subpart C	110.88	27.72